



CLARUS RADIUS LED, EU

Recessed Downlight - Adjustable high power LED with 13mm (1/2") trim and milled aluminum apure© louver. High performance Cree LEDs combined with precision optics for maximum performance. LED lifetime rated for 50,000 hours, given electrical specifications are met.

Construction

- Formed steel lamp holder with 360° rotation and 40° adjustment from nadir, via double-axis pivot for maximum center beam optical performance.
- Formed steel trim with powder coat paint finish combined with signature aluminum apure© louver, available in various colors and combinations.
- 300mA LED driver required for optimal performance and LED longevity.
- Made in Germany, Design by Porsche Design Studio.

Lamp Module

- 11W Cree LED module, includes integrated heat sink, and LED holder with adapter compatible with apure LED reflectors.

ORDERING INFORMATION

SERIES NO.	ADJUSTABLE	TRIM FINISH	LOUVER FINISH	COLOR TEMP.	DRIVER
AP91 - 11W LED downlight with trim	A - adjustable downlight	WH - white BL - black CC - custom	WH - white powder coat NA - natural anodized BA - black anodized TI - titan anodized GO - gold anodized BR - bronze anodized GM - gun metal anodized RG - rose gold anodized	3080 - 3000K (80 CRI) 3090 - 3000K (90+ CRI)	EU - requires transformer

AP91A- __ / __ - ____ - EU

ORDERING EXAMPLE AP91A-WH/NA-3080-EU

Related Accessories (one reflector per fixture required)

- AA0-10 - 10° aluminum LED reflector
- AA0-17 - 17° metalized molded plastic LED reflector
- AA0-24 - 24° metalized molded plastic LED reflector
- AA0-25 - 25° aluminum LED reflector
- AA0-36 - 36° metalized molded plastic LED reflector
- AA0-45 - 45° aluminum LED reflector
- AA3-300 - 300mA Driver (120-277V)

Mounting

- Mounts to ceiling via European torsion spring.

Additional Information

- 300mA driver available for purchase (AA3-300) as a separate accessory for use with LED fixtures.
- Damp location.
- Cutout dimension - 110mm
- Minimum ceiling depth - 100mm