



Project:	Type:
----------	-------

## Accessories

Required Accessories	Part Number	Cutsheet Available	Release Date
Drywall Universal Bracket	AA2-BRK-U	Yes	Available
Apure Power Supply (100W 24VDC)	AA3-100-L	Yes	Available
Lutron Hi-Lume Premier Ecosystem Driver	L3D0-96W24V-U	Yes, Lutron.com	Q3 2018

## Custom Installation Types

- The universal bracket (AA2-BRK-U) is intended only for drywall installations.
- Speak to an authorized Minus reseller for more information about custom ceiling integrations.
- System ceilings, stone, wood, and metal ceiling integrations are accomplished through custom fabrication by others.
- While Apure will make every effort to accommodate custom integrations, there are restrictions and not all materials are suitable for installations.
- Fixture must have a **minimum clearance** of 6 inches (15cm) below or horizontally from the light source at all times!
- Observe and follow all local and NEC codes in all installation types.
- Before any mudding, finishing or painting - test all fixtures are functioning properly!
- Read and adhere to all instructions supplied with each power supply and fixture!

## Wiring Diagram

- Minus fixtures are to be wired to the power supply using min. 16AWG cable via parallel wiring.
- Follow all instructions supplied by power supply / driver manufacturer!
- Operation of up to 5 fixtures requires one 96-100W power supply.
- Follow all instructions supplied by power supply / driver manufacturer!
- Before any mudding, finishing or painting - test that all fixtures are functioning properly!

